



# TOPAZ



## TZWL 35

### BOPP & PVC Film Lamination

#### Description:

Topaz TZWL 35 is an aqueous dispersion of polyvinyl acetate-acrylate Co polymers developed for BOPP & PVC film print lamination.

#### Characteristics:

Appearance	: Milky White
Polymers type	: Emulsion
Solid content	: 34 - 36%
Brook field Viscosity	: 2000 – 5000 cPs
RVDV-E Sp 4/20	
pH	: 4 - 6
Film Properties	: Transparent

#### Properties & Applications:

Topaz TZWL 35 is a medium viscosity economy product having good flow Good wetting and good machinability.

Topaz TZWL 35 is suitable adhesive for BOPP/

PVC film & printed paper /board lamination which gives glossy and clear coating with good bond strength.

#### Storage & Handling:

Topaz TZWL 35 can be stored in poly lined or SS containers. To have a longer shelf life the container should be kept tightly closed in cool but frost free place. The product can be easily washed off with water before the film dries up. In some case warm water with little scrubbing is required. In the event of the product coming in the direct contact with eyes or skin washing with plenty of water should be restored. For any abnormal symptoms seek medical advice.

**Stability:** Topaz TZWL 35 has a long shelf life of 6 months provided it is stored in cool place.

**Packing:** Topaz TZWL 35 is available in 50 Kgs & 225 Kgs.

## Kapoor Imaging Pvt. Ltd.

3, Masilamani Road, Balaji Nagar, Royapettah  
Chennai - 600 014, INDIA  
Phone : +91 44 4347 1000, Fax : +91 44 4347 1020  
Email : sales@kapoorimaging.com  
Website : www.kapoorimaging.com

Distributor