



TOPAZ



TOPONOL

Printing Grade IPA

Description:

TOPAZ Toponol is used in combination with fountain and water for better wet ability and consistent Ink Water Balance of improve drying. Standard dosage for Printing Industry 6 -8 % Used as a dampening additive in alcohol dampening unit and reduces surface tension. It increases fountain solution transport to inking plate and inking unit. Increases viscosity of fountain solution. Faster wetting on plate .Less ink build up on dampening rollers. Cooling effect in the Printing Grade IPA press / chiller unit because of evaporation.

Features:

- Used as a dampening additive in alcohol dampening unit and reduces surface tension

Kapoor Imaging Pvt. Ltd.

3, Masilamani Road, Balaji Nagar, Royapettah
Chennai - 600 014, INDIA
Phone : +91 44 4347 1000, Fax : +91 44 4347 1020
Email : sales@kapoorimaging.com
Website : www.kapoorimaging.com

- It increases fountain solution transport to inking plate and inking unit.
- Increases viscosity of fountain solution.
- Faster wetting of plate .
- Less ink build up on dampening rollers.
- Cooling effect in the press / chiller unit because of evaporation.

Specifications:

Standard dosage for Printing Industry 6-8% and for other Industry as per the requirement

Flash point : 12°C

Density : 0,780 gm/cm³

Solubility in water - Miscible in all proportion

Distributor